

86740/86750 2/2-way piston valves

- Port size: DN 8 ... 50, G1/4 ... 2 (ISO G/NPT)
- Valve operates without differential pressure (Zero delta P)
- Valve piston with PTFE guide-ring
- Suitable for vacuum
- Damped operation
- International approvals



Technical features

Medium:
Slightly aggressive gases and liquids

Switching function:
Normally closed

Operation:
Solenoid actuated, with forced lifting

Mounting:
Optional, preferably solenoid vertical on top

Flow direction:
Determined

Port size:
G1/4, G3/8, G1/2, G3/4, G1, G1 1/4, G1 1/2, G2
1/4 NPT, 3/8 NPT, 1/2 NPT, 3/4 NPT, 1 NPT, 1 1/4 NPT, 1 1/2 NPT, 2 NPT

Operating pressure:
0 ... 25 bar (0 ... 362 psi)
0 ... 40 bar (0 ... 580 psi)


Fluid temperature:
-20 ... +90°C (-4 ... +194°F)

Ambient temperature:
-20 ... +50°C (-4 ... +122°F)

Material:
Body: Stainless steel (1.4408)
Seat seal: NBR
Internal parts: Stainless steel, PTFE / Carbon

For contaminated fluids insertion of a strainer is recommended.

Technical data – standard models

Symbol	Port size	Orifice (mm)	Flow kv value *1) (m³/h)	Operating pressure *2) (bar) (psi)		Weight (kg)	Model Solenoid in V d.c.	Model Solenoid in V a.c.
	G1/4	8	2,2	0 ... 25	0 ... 362	2,4	8674000.8301.xxxxx	8674000.8304.xxxxx
	1/4 NPT	8	2,2	0 ... 25	0 ... 362	2,4	8675000.8301.xxxxx	8675000.8304.xxxxx
	G3/8	10	3,4	0 ... 25	0 ... 362	2,4	8674100.8301.xxxxx	8674100.8304.xxxxx
	3/8 NPT	10	3,4	0 ... 25	0 ... 362	2,4	8675100.8301.xxxxx	8675100.8304.xxxxx
	G1/2	12	4,4	0 ... 25	0 ... 362	2,5	8674200.8301.xxxxx	8674200.8304.xxxxx
	1/2 NPT	12	4,4	0 ... 25	0 ... 362	2,5	8675200.8301.xxxxx	8675200.8304.xxxxx
	G3/4	20	6,5	0 ... 25	0 ... 362	2,7	8674300.8301.xxxxx	8674300.8304.xxxxx
	3/4 NPT	20	6,5	0 ... 25	0 ... 362	2,7	8675300.8301.xxxxx	8675300.8304.xxxxx
	G1	25	10	0 ... 25	0 ... 362	3,1	8674400.8301.xxxxx	8674400.8304.xxxxx
	1 NPT	25	10	0 ... 25	0 ... 362	3,1	8675400.8301.xxxxx	8675400.8304.xxxxx
	G1 1/4	32	24	0 ... 25	0 ... 362	5,6	8674500.8401.xxxxx	8674500.8404.xxxxx
	1 1/4 NPT	32	24	0 ... 25	0 ... 362	5,6	8675500.8401.xxxxx	8675500.8404.xxxxx
	G1 1/2	40	25	0 ... 25	0 ... 362	5,4	8674600.8401.xxxxx	8674600.8404.xxxxx
	1 1/2 NPT	40	25	0 ... 25	0 ... 362	5,4	8675600.8401.xxxxx	8675600.8404.xxxxx
	G2	50	41	0 ... 25	0 ... 362	6,8	8674700.8401.xxxxx	8674700.8404.xxxxx
	2 NPT	50	41	0 ... 25	0 ... 362	6,8	8675700.8401.xxxxx	8675700.8404.xxxxx

xxxxx Please insert voltage and frequency codes

*1) Cv-value (US) ≈ kv value x 1,2

*2) For gases and liquid fluids up to 40 mm²/s (cSt)

Option selector

867★★★★★.★★★★★.★★★★★

Gewindeform	Substitute
ISO G	4
NPT	5
Port size	Substitute
1/4	0
3/8	1
1/2	2
3/4	3
1	4
1 1/4	5
1 1/2	6
2	7
Valve options	Substitute
Normally open (NO), Mounting position: Solenoid vertical on top	01
Manual override, only with solenoid 84xx	02
Seat seal FPM, Fluid temperature -10 ... +110°C *3) (+14 ... +230°F)	03
Seat seal PTFE, Fluid temperature -20 ... +110°C *3) (-4 ... +230°F), Leakage rate E acc. to DIN EN 12266-1	06
Seat seal EPDM, for hot water, Fluid temperature -20 ... +110°C (-4 ... +230°F)	14
Normally open (NO), Seat seal FPM, Fluid temperature -10 ... +110°C *3) (+14 ... +230°F), Mounting position: Solenoid vertical on top	17

Frequency	Substitute
See table frequency codes	xx
Voltage	Substitute
See table voltage codes	xxx
Solenoid options	Substitute
G1/4 ... 1 Solenoid in V d.c.	8301
G1 1/4 ... 2 Solenoid in V d.c.	8401
G1/4 ... 1 Solenoid in V a.c.	8304
G1 1/4 ... 2 Solenoid in V a.c.	8404
Valve options	Substitute
Max. operating pressure 40 bar, only with solenoid 84xx	22
Electrical position indicator with 2 limit switches (Reed contact) only with solenoid 84xx	23
Seat seal FPM, with larger bleed orifices in the piston, for fluids such as fuel and oil, viscosity max. 80 mm ² /s (cSt), Fluid temperature -10 ... +110°C *3) (+14 ... +230°F), only with solenoid 84xx	25
Designed for ammonia, Seat seal CR	75
Version for drinking water on request	

Standard solenoid systems

Voltage and Frequency Solenoid 8301/8304					
Code	Code	Voltage	Frequency	Power consumption	
Voltage	Frequency			Inrush	Holding
024	00	24 V d.c.	-	22 W	22 W
024	49	24 V a.c. *3)	40 ... 60 Hz	25 VA	25 VA
110	49	110 V a.c. *3)	40 ... 60 Hz	25 VA	25 VA
120	49	120 V a.c. *3)	40 ... 60 Hz	25 VA	25 VA
230	49	230 V a.c. *3)	40 ... 60 Hz	25 VA	25 VA
Voltage and Frequency Solenoid 8401/8404					
024	00	24 V d.c.	-	40 W	40 W
024	49	24 V a.c. *3)	40 ... 60 Hz	45 VA	45 VA
110	49	110 V a.c. *3)	40 ... 60 Hz	45 VA	45 VA
120	49	120 V a.c. *3)	40 ... 60 Hz	45 VA	45 VA
230	49	230 V a.c. *3)	40 ... 60 Hz	45 VA	45 VA

*3) a.c. only with rectifier plug

Further versions on request!

Electrical details for all solenoid systems

Design	DIN VDE 0580
Voltage range	±10%
Duty cycle	100% ED
Protection class	EN 60529 IP65
Socket	Form A acc. to DIN EN 175301-803 (included)

According to DIN VDE 0580 at a solenoid temperature of +20°C (+68°F).
At operating state temperature the input power of a coil decreases by up to ca. 30% due to physical reasons.

Additional solenoid systems for hazardous areas

ATEX category	ATEX protection class	IP protection class	Solenoid	Standard voltages
II 3G II 3D	Ex ec IIC T4 Gc Ex tc IIIC T130°C DC	IP65	8326 *4)	24 V d.c.
II 3G II 3D	Ex ec IIC T4 Gc Ex tc IIIC T130°C DC	IP65	8426 *4)	24 V d.c.
II 2G II 2D	Ex eb mb IIC T3 Gb Ex mb tb IIIB T135°C Db	IP66	6220	24 V d.c., 110 V a.c., 230 V a.c.
II 2G II 2D	Ex eb mb IIC T3 Gb Ex mb tb IIIB T140°C Db	IP66	6240	24 V d.c., 110 V a.c., 230 V a.c.

Attention!


The conditions imposed on the Ex approvals lead to reduction of the permissible standard temperature ranges in the cases of explosion protected solenoids.

*4) d.c. only, for a.c. solenoids with design inspection certificate acc. to category 2, e.g. 6220 oder 6240

Dimensions

G1/4 ... 1
1/4 ... 1 NPT

Dimensions in mm
Projection/first angle




- 1 Solenoid rotatable 360°
- 2 Socket turnable 4 x 90°
(Socket included)

Port size R	ø A	H	H1	L	L1	T	Model
G1/4	44	143	132	60	27,5	12	8674000.830x.xxxxx
1/4 NPT	44	143	132	60	27,5	10	8675000.830x.xxxxx
G3/8	44	143	132	60	27,5	12	8674100.830x.xxxxx
3/8 NPT	44	143	132	60	27,5	10,5	8675100.830x.xxxxx
G1/2	44	145	132	67	31	14	8674200.830x.xxxxx
1/2 NPT	44	145	132	67	31	13,5	8675200.830x.xxxxx
G3/4	50	154	137	80	35,5	16	8674300.830x.xxxxx
3/4 NPT	50	154	137	80	35,5	14	8675300.830x.xxxxx
G1	62	164	143,5	95	44	18	8674400.830x.xxxxx
1 NPT	62	164	143,5	95	44	17	8675400.830x.xxxxx

Dimensions

G1 1/4 ... 2
1 1/4 ... 2 NPT

Dimensions in mm
Projection/first angle



- 1 Solenoid rotatable 360°
- 2 Socket turnable 4 x 90°
(Socket included)

Port size R	ø A	H	H1	L	L1	T	Model
G1 1/4	92	212,5	183,5	132	60	20	8674500.840x.xxxxx
1 1/4 NPT	92	212,5	183,5	132	60	17	8675500.840x.xxxxx
G1 1/2	92	212,5	183,5	132	60	22	8674600.840x.xxxxx
1 1/2 NPT	92	212,5	183,5	132	60	17	8675600.840x.xxxxx
G2	109	226,5	192	160	74	24	8674700.840x.xxxxx
2 NPT	109	226,5	192	160	74	17,5	8675700.840x.xxxxx

Note to Pressure Equipment Directive (PED):

The valves of this series up to and including DN 25 (G1) are according to Art. 4 § 3 of the Pressure Equipment Directive (PED) 2014/68/EU. This means interpretation and production are in accordance to engineers practice wellknown in the member countries. The CE-sign at the valve does not refer to the PED. Thus the declaration of conformity is not longer applicable for this directive.

For valves > DN 25 (G1) Art. 4 § (1) Letter d) applies:

The basic requirements of the Enclosure I of the PED must be fulfilled. The CE-sign at the valve includes the PED. A certificate of conformity of this directive will be available on request.

Note to Electromagnetic Compatibility Guideline (EEC):

The valves shall be provided with an electrical circuit which ensures the limits of the harmonised standards EN 61000-6-3 and EN 61000-6-1 are observed, and hence the requirements of the Electromagnetic Compatibility Guideline (2014/30/EU) satisfied.

Note to EAC marking:

The EAC-marked products comply with the applicable requirements stated in the technical regulations of the Eurasian Economic Union.